RSA-DB 4-188

4" ROUND STRAIGHT ALUM. (0.188 Heavy Wall)

POLES & LIGHTING

Job Name: _____ Location: _____ Quote: _____

Client Name: _____ Type: _____ Quote Date: _____

AV POLES & LIGHTING
43827 Division St.
Lancaster, CA 93535
Toll Free: (844) 770-AVPL
Fax: (661) 945-2764
sales@avpltg.com
www.avpltg.com





SUITABLE FOR WET LOCATIONS

DBZ BLK WHT GRY GRN

SHAFT: One-piece extruded 6063 aluminum alloy tube heat treated to a T6 temper.

GROUNDING: Provision; 3/8-16 Threaded stud welded to inner shaft wall opposite hand hole. Flat washer and hex nut provided.

HARDWARE: S304 stainless steel

FINISH: TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil minimum thickness. A five stage metal pretreatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.

POLE SCHEDULE

CATALOG NUMBER	POLE HEIGHT	SHAFT SIZE	WALL THICKNESS	DIRECT BURIAL
RSA-DB-144-188	14'	Ø4"	0.188"	Extends 48" below grade
RSA-DB-164-188	16'	Ø4"	0.188"	Extends 48" below grade
RSA-DB-184-188	18'	Ø4"	0.188"	Extends 48" below grade

E.P.A. DATA SCHEDULE

Calculations based on sustained wind forces plus additional 1.3 mph gust.

MAX. FIXT. WT.	70 MPH	80 MPH	90 MPH	100 MPH
N/A	N/A	N/A	N/A	N/A
N/A	N/A	N/A	N/A	N/A
N/A	N/A	N/A	N/A	N/A

TENON OR DRILL MOUNT

TENON MOUNT: Available with 2.375", 2.875", or 3.00" O.D. tenon

DRILL MOUNT: Removable top cap provided with drill-mount poles



GFI RECEPTACLE

GFI-METAL COVER: 2 gang vertical GFI receptacle with NEC 2017 Section 406.9(B)(1) compliant metal cover.

GFI-WEATHER PROOF IN-USE COVER: 2 gang vertical GFI receptacle with In Use Non Metallic cULus listed cover.



HAND HOLE

HAND HOLE: Reinforced 3" x 5" hand hole is located 18" above base. Cover and attachment hardware provided.



DIRECT BURIAL

DIRECT BURIAL: Direct burial poles are placed directly in ground material, eliminating the need for anchor plates and anchor bolt requirements. Fabricated with two anti-rotation fins and Ø2" conduit opening for electrical access.



ORDERING INFORMATION

RSA-DB - _____ - _____ - _____ - _____ - _____ - _____ - _____

HEIGHT	SHAFT	SHAFT WALL	MOUNTING	GFI	ACCESSORIES	FINISH
14'	**4"** Ø4" Round	**0.188"** Heavy Wall	**PT23** Ø2.375" TENON	**GFI** with METAL COVER	**BEB** BANNER EYE BOLT	**DBZ** DARK BRONZE
16'			**PT27** Ø2.875" TENON	**GFI** with WEATHER PROOF IN-USE COVER	**CPLN** THREADED COUPLING	**BLK** BLACK
18'			**PT30** Ø3.00" TENON		**BA** BANNER ARMS	**WHT** WHITE
			1@90 POLE DRILLING		**BH** BASKET HOLDERS	**GRY** GREY
			2@90 POLE DRILLING		**FH** FLAG HOLDERS	**GRN** GREEN
			2@180 POLE DRILLING			**ANOD** ANODIZED
			3@90 POLE DRILLING			
			4@90 POLE DRILLING			
CONTACT FACTORY FOR HEIGHT OPTIONS			CONTACT FACTORY FOR DRILLING OPTIONS		CONTACT FACTORY FOR DETAILS	ALL RAL COLORS AVAILABLE