




SAVANNAH BASE (1 PIECE)



DESCRIPTION

The SAV base is ideal for courtyards, pathways, municipal, and commercial decorative light pole applications.

FEATURES

Welds to 4" or 5" O.D. smooth or fluted round aluminum shafts.

One piece corrosion resistant cast aluminum construction with minimum wall thickness of .375"

Hand hole fabricated into base.

Stainless steel hardware.

Anchor bolts are fabricated from hot-rolled carbon steel bar with minimum yield strength of 55,000 PSI. Bolts are fully galvanized and conform to ASTM-F1554 A55. Each bolt is furnished with two hex nuts and two flat washers.

TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.



SUITABLE FOR
WET
LOCATIONS

ORDERING INFORMATION

AVPL -	BASE	SHAFT	HEIGHT	SHAFT WALL	MOUNTING	FINISH	ACCESSORIES
	SAV	4S Ø4" SMOOTH 4F Ø4" FLUTED 5S Ø5" SMOOTH 5F Ø5" FLUTED	10' 12' 14' 16' 18'	.125" .188"	PT23 Ø2.375" TENON PT27 Ø2.875" TENON POLE DRILLING	DARK BRONZE BLACK WHITE GREY GREEN	GFI with IN-USE COVER BEB BANNER EYE BOLT CPLN THREADED COUPLING BA BANNER ARMS BH BASKET HOLDERS FH FLAG HOLDERS
			CONTACT FACTORY FOR HEIGHT OPTIONS		CONTACT FACTORY FOR DRILLING OPTIONS	ALL RAL COLORS AVAILABLE	CONTACT FACTORY FOR DETAILS