



	<b>LA-1</b> 1	Туре:	Client Name: Quote: Quote Date:	AV POLES & LIGHTING 43827 Division St. Lancaster, CA 93535 Toll Free: (844) 770-AVPL Fax: (661) 945-2764 sales@avpltg.com www.avpltg.com
	LOS ANG	ELES 11 BASI		
			DESCRIPTION The LA-11 base is ideal for courtyards, pathways, municipal, and commercial decorative light pole applications. FEATURES	
			Welds to 4"or 5" O.D. smooth or fluted round aluminum shafts.	
•			One piece corrosion resistant with minimum wall thickness o	
			Hand hole fabricated into ba	se.
		18' MAX	Stainless steel hardware.	
			Anchor bolts are fabricated fr bar with minimum yield streng fully galvanized and conform Each bolt is furnished with two washers.	th of 55,000 PSI. Bolts are to ASTM-F1554 A55.
]4" J	Bolt Projection 3.25" - 3.75"		TGIC thermoset polyester pov electrostatically applied at a A five stage metal pre-treatma provide maximum corrosion r coat is baked in excess of 40	3.0 mil nominal thickness. ent process and sealer esistance. The powder top

24.5"





DETAIL

## **ORDERING INFORMATION**

Ø14"

endurance.



AVPL -SHAFT HEIGHT SHAFT WALL MOUNTING FINISH ACCESSORIES BASE DARK BRONZE LA-11 **4**S 10' .125" PT23 GFI Ø4" SMOOTH with IN-USE COVER Ø2.375" TENON 12' .188" PT27 BLACK BEB **4**F Ø4" FLUTED Ø2.875" TENON BANNER EYE BOLT **5S** 14' POLE WHITE CPLN Ø5" SMOOTH DRILLING THREADED COUPLING 5F 16' GREY BA Ø5" FLUTED BANNER ARMS 18' GREEN BH BASKET HOLDERS **FH** FLAG HOLDERS CONTACT CONTACT CONTACT FACTORY FOR DETAILS FACTORY FOR HEIGHT OPTIONS FACTORY FOR DRILLING OPTIONS ALL RAL COLORS AVAILABLE