

HRG	Туре:	Client Name: Quote: Quote Date:	AV POLES & LIG 43827 Division S Lancaster, CA 93 Toll Free: (844) 7 Fax: (661) 945-2 sales@avpltg.co www.avpltg.com
HOUR	GLASS BASE (1		
		The HRG base is pathways, munici	RIPTION ideal for courtyards, pal, and commercial pole applications.
0.0/		FEA	TURES
		Welds to 4", 5", or 6" O.E). smooth or fluted round


aluminum shafts.

One piece corrosion resistant cast aluminum construction with minimum wall thickness of .210"

Hand hole fabricated into base.

Stainless steel hardware.

TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.



AVPL -

ANCHOR BOLT

DETAIL

ORDERING INFORMATION

Ø16"

20.25"

18'

MAX

2	SUITABLE FOR
J	LOCATIONS

SHAFT WALL ACCESSORIES BASE SHAFT HEIGHT MOUNTING FINISH HRG **4**S 10' .125" PT23 DARK BRONZE GFI Ø4" SMOOTH with IN-USE COVER Ø2.375" TENON 12' .188" BLACK **4**F PT27 BEB Ø4" FLUTED Ø2.875" TENON BANNER EYE BOLT **5**S 14' POLE WHITE CPLN Ø5" SMOOTH DRILLING THREADED COUPLING 5F GREY 16' ΒA Ø5" FLUTED BANNER ARMS 6S 18' GREEN BH Ø6" SMOOTH BASKET HOLDERS **6F** Ø6" FLUTED FH FLAG HOLDERS CONTACT CONTACT CONTACT FACTORY FOR HEIGHT OPTIONS FACTORY FOR DRILLING OPTIONS ALL RAL COLORS AVAILABLE FACTORY FOR DETAILS



AV POLES & LIGHTING 43827 Division St. Lancaster, CA 93535 Toll Free: (844) 770-AVPL Fax: (661) 945-2764 sales@avpltg.com www.avpltg.com