



Job Name:	Client Name
Job Location:	Quote:

Type: Quo


Quote:

Quote Date:


AV POLES & LIGHTING 43827 Division St. Lancaster, CA 93535 Toll Free: (844) 770-AVPL Fax: (661) 945-2764 sales@avpltg.com www.avpltg.com

FRONTIER BOLLARD






ANCHORAGE



Anchor Bolt 2" Minimum Projection



Anchor Plate 8" Square 5.5" B.C.D. 4" Conduit Opening

DESCRIPTION

An outstanding traditional design and authentic appearance that is suitable for a variety of lighting applications. The FRN-BOL series by AV Poles and Lighting is ideal for courtyards, pathways, and all low level lighting applications.

FEATURES

- Square extruded and cast aluminum construction
- Stainless steel hardware
- Acrylic injection molded lenses with smooth opal finish.
- 0-10V dimmable driver
- 10-20KV surge protection
- IP67 rated modules 5 year warranty
- Up to 180 Lumens Per Watt output
- Low maintenance cost with lifetime >54,000 hrs
- LED modules arranged in a Type V optic pattern for even light distribution.
- TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.











ORDERING INFORMATION

AVPL - _____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ - ____ - ___

BOLLARD	HEIGHT	WATTAGE	COLOR TEMP	VOLTAGE	LENS COVER	FINISH	OPTIONS
FRN-BOL	42"	18W 350mA	3000K WARM WHITE	120-277V VOLTAGE SENSING	Type A	DARK BRONZE	STANCHION MOUNT
		26W 525mA	4000K NEUTRAL WHITE	347-480V VOLTAGE SENSING		BLACK	HOUSE-SIDE SHIELD
		36W 700mA	5000K COOL WHITE		Type B	WHITE	PHOTOCELL BUTTON
		52W 1050mA				GREY	
					Type C	GREEN	
					38		
					Type D		
					APPLY LLF OF 10% TO LUMEN OUTPUT CHART	ALL RAL COLORS AVAILABLE	

LUMEN OUTPUT CHART

$\overline{\mathbf{Y}}$		18W 350mA	26W 525mA	36W 700mA	52W 1050mA	¥		18W 350mA	26W 525mA	36W 700mA	52W 1050mA	¥		18W 350mA	26W 525mA	36W 700mA	52W 1050mA
က	Type V	2,462	3,349	4,348	5,865	7	Type V	2,592	3,515	4,579	6,156	9	Type V	2,61 <i>7</i>	3,550	4,624	6,217