





AVPL ENV - SS Architectural Bell Luminaire

Description

Decorative architectural design provides a unique lighting solution for a variety of applications. The ENVSS series by AV Poles and Lighting is ideal for commercial, municipal, and design build lighting applications.

Features

- Spun Aluminum construction
- Stainless Steel hardware
- Dark Sky/ Full Cutoff
- IP67 rated modules - 5 year warranty
- Up to 130+ Lumens Per Watt output
- Low maintenance cost with lifetime >54,000 hrs
- Multiple lighting distribution options with optical lens transmittance up to 98%
- Multiple LED modules can easily be connected in series
- TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.



Ordering Information

| Luminaire | Lamp Type | Volts | Mounting | Finish | Options | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|--|-------------------------------|---|-------------------------------|-------------------------------|---------|------------------------------|--|-------------------------------|-------------------------------|---|---|---|--|--------|---------|-------|-------|-------|--------|--------|-------|-------|-------|--------|--|---------------|------------|---------------|------------|---------|--------|--------|--------|--------|----------|--------|--------|--------|--------|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--|--|--|--|
| <input type="checkbox"/> AVPL ENVSS1 <input type="checkbox"/> AVPL ENVSS2 | LED <small>*Please call factory for alternate lamp options*</small> <table border="0"> <tr> <td>700mA</td> <td><input type="checkbox"/> 35W</td> <td><input checked="" type="checkbox"/> 71W</td> <td><input type="checkbox"/> 104W</td> <td><input type="checkbox"/> 136W</td> </tr> <tr> <td>1A</td> <td><input type="checkbox"/> 55W</td> <td><input checked="" type="checkbox"/> 106W</td> <td><input type="checkbox"/> 156W</td> <td><input type="checkbox"/> 205W</td> </tr> </table> <p><input checked="" type="checkbox"/> = ENVSS2 MAX Wattage</p> | 700mA | <input type="checkbox"/> 35W | <input checked="" type="checkbox"/> 71W | <input type="checkbox"/> 104W | <input type="checkbox"/> 136W | 1A | <input type="checkbox"/> 55W | <input checked="" type="checkbox"/> 106W | <input type="checkbox"/> 156W | <input type="checkbox"/> 205W | <input type="checkbox"/> 120 <input type="checkbox"/> 208 <input type="checkbox"/> 240 <input type="checkbox"/> 277 <input type="checkbox"/> MT | <input type="checkbox"/> Wall Mount..... <input type="checkbox"/> 1..... <input type="checkbox"/> 2-90..... <input type="checkbox"/> 2-180..... <input type="checkbox"/> 3-90..... <input type="checkbox"/> 3-120..... <input type="checkbox"/> 4-90..... | <input type="checkbox"/> Dark Bronze <input type="checkbox"/> Black <input type="checkbox"/> White <input type="checkbox"/> Grey <input type="checkbox"/> Green | Optical <input type="checkbox"/> House Side Shield Electrical <input type="checkbox"/> 10-20KV Surge Protector <input type="checkbox"/> 0-10V Dimmable Driver(s) <input type="checkbox"/> Photo Cell + Voltage <input type="checkbox"/> High/Low Dimming for Hardwired Switching or Non-Integrated Motion Sensor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 700mA | <input type="checkbox"/> 35W | <input checked="" type="checkbox"/> 71W | <input type="checkbox"/> 104W | <input type="checkbox"/> 136W | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1A | <input type="checkbox"/> 55W | <input checked="" type="checkbox"/> 106W | <input type="checkbox"/> 156W | <input type="checkbox"/> 205W | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Optics | <table border="1"> <thead> <tr> <th></th> <th>35W 700mA</th> <th>55W 1A</th> <th>71W 700mA</th> <th>106W 1A</th> </tr> </thead> <tbody> <tr> <td>Type II</td> <td>4,424</td> <td>6,017</td> <td>8,848</td> <td>12,033</td> </tr> <tr> <td>Type III</td> <td>4,558</td> <td>6,199</td> <td>9,116</td> <td>12,398</td> </tr> <tr> <td>Type IV</td> <td>4,381</td> <td>5,958</td> <td>8,762</td> <td>11,916</td> </tr> <tr> <td>Type V</td> <td>4,432</td> <td>6,028</td> <td>8,864</td> <td>12,055</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th></th> <th>104W 700mA</th> <th>156W 1A</th> <th>136W 700mA</th> <th>205W 1A</th> </tr> </thead> <tbody> <tr> <td>Type II</td> <td>13,272</td> <td>18,050</td> <td>17,696</td> <td>24,067</td> </tr> <tr> <td>Type III</td> <td>13,674</td> <td>18,597</td> <td>18,232</td> <td>24,796</td> </tr> <tr> <td>Type IV</td> <td>13,143</td> <td>17,874</td> <td>17,524</td> <td>23,833</td> </tr> <tr> <td>Type V</td> <td>13,296</td> <td>18,083</td> <td>17,728</td> <td>24,110</td> </tr> </tbody> </table> | | 35W 700mA | 55W 1A | 71W 700mA | 106W 1A | Type II | 4,424 | 6,017 | 8,848 | 12,033 | Type III | 4,558 | 6,199 | 9,116 | 12,398 | Type IV | 4,381 | 5,958 | 8,762 | 11,916 | Type V | 4,432 | 6,028 | 8,864 | 12,055 | | 104W 700mA | 156W 1A | 136W 700mA | 205W 1A | Type II | 13,272 | 18,050 | 17,696 | 24,067 | Type III | 13,674 | 18,597 | 18,232 | 24,796 | Type IV | 13,143 | 17,874 | 17,524 | 23,833 | Type V | 13,296 | 18,083 | 17,728 | 24,110 | <input checked="" type="checkbox"/> = LED Only | | | |
| | 35W 700mA | 55W 1A | 71W 700mA | 106W 1A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type II | 4,424 | 6,017 | 8,848 | 12,033 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type III | 4,558 | 6,199 | 9,116 | 12,398 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type IV | 4,381 | 5,958 | 8,762 | 11,916 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type V | 4,432 | 6,028 | 8,864 | 12,055 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 104W 700mA | 156W 1A | 136W 700mA | 205W 1A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type II | 13,272 | 18,050 | 17,696 | 24,067 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type III | 13,674 | 18,597 | 18,232 | 24,796 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type IV | 13,143 | 17,874 | 17,524 | 23,833 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type V | 13,296 | 18,083 | 17,728 | 24,110 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Color Temp <input type="checkbox"/> 3000K Warm <input type="checkbox"/> 4000K Neutral <input type="checkbox"/> 5000K Cool | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |