

MBL SERIES - LED BOLLARD

The MBL01 SERIES - LED Bollard Light, 119 lm/W, IP65 Wet Location, 0-10V Dimmable, Premium Outdoor Luminaire.

FEATURES

Lumen Output	3100 lumens
Efficacy	119 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	4000K or 5000K
IP Rating	IP65 Wet Location
Warranty	5 Years

Applications

Premium outdoor luminaire suitable for building entrances, pathways, boardwalks, and pedestrian walkways.

Construction

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. IP65 Wet Location rated for dust-tight, water jets: IEC 60529.

Electrical

Input voltages 120-277V with 0-10V Continuous Dimming. Operating temperatures -40°F to 113°F (-40°C to 45°C).

Mounting

Integrated ground stakes for round cage pre-buried installation.

Optics

Anti-UV Clear Polycarbonate Lens with reflective inner cup.

Listings

UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. Listed to qualify for energy-efficient LED lighting rebates.

Warranty

5 yr /50K hrs.



Correlated Color Temperatures (CCT)

4000K

5000K



SPECIFICATIONS

Energy Data

Input Voltage:	120-277V
Input Frequency:	50/60 Hz
Wattage:	26W
Power Factor:	>0.9
Operating Temperature:	-40°F to 113°F (-40 °C to 45°C)

Lighting Data

Lumens:	3100
Lumens Per Watt:	119 lm/W
Color Correlated Temperature (CCT):	4000K, 5000K
Dimmable:	0-10V
Color Rendering Index (CRI):	>80
L70:	50000 hours

ORDERING INFORMATION


Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
MBL01-26W-4000K	26W	120-277V	0.22A@120V, 0.09A@277V	3100	119 lm/W	4000K	0-10V	Dark Bronze	ø 9.28" C (Head) 42.00" L x ø 5.50" C (Body) 50.62" L (Total w/ Ground Stakes)
MBL01-26W-5000K	26W	120-277V	0.22A@120V, 0.09A@277V	3100	119 lm/W	5000K	0-10V	Dark Bronze	ø 9.28" C (Head) 42.00" L x ø 5.50" C (Body) 50.62" L (Total w/ Ground Stakes)

SHIPPING INFORMATION


Model Size	Shipping Dimensions	Shipping Weight	Quantity Per Box
26W	46.00" L x 11.00" W x 11.00" D	17.00 lbs	1

DIMENSIONS

26W Model



PHOTOMETRIC DATA



*Example of 26W 5000K

