



POLES & LIGHTING

43827 Division St.
Lancaster, CA 93535
Toll free: (844) 770-AVPL
Fax: (661) 945-2764
sales@avpltg.com
www.avpltg.com

Screw-In LED Lamp List

ITEM#	DESCRIPTION	WATTS	CCT	LM	LM/W	BEAM	CRI	MOL	MOD	VOLTS	LIFE	TRAD. EQUIV.	CASE
90779	LED 12WT22/360°/CL/50K/MED 100-300V	12	50K	1300	108	360°	80	6.5"	2.8"	100-300	50K	40W	12
91122	LED 14WT22/320°/CL/50K/MED/120-277V/V4 - SL®	14	50K	1500	107	320°	80	5.7"	2.8"	120-277	50K	45W	24
91575	LED 16WT19/360°/CL/50K/MED/120-277V/V5 - SL®	16	50K	2080	130	360°	80	6.5"	2.4"	120-277	50K	50W	12
90781	LED 16WT22/360°/STREET LIGHT/50K/MED-100-300V	16	50K	1750	109	360°	80	6.9"	2.8"	100-300	50K	50W	12
91690	LED 22WT19/360°/CL/30K/MED/120-277V/V5 - SL®	22	30K	2860	130	360°	80	7.1"	2.4"	120-277	50K	60W	12
91576	LED 22WT19/360°/CL/50K/MED/120-277V/V5 - SL®	22	50K	2860	130	360°	80	7.1"	2.4"	120-277	50K	60W	12
91691	LED 27WT30/360°/CL/30K/MED/120-277V/V5 - SL®	27	30K	3510	130	360°	80	7.3"	3.7"	120-277	50K	120W	12
91577	LED 27WT30/360°/CL/50K/MED/120-277V/V5 - SL®	27	50K	3510	130	360°	80	7.3"	3.7"	120-277	50K	120W	12
91692	LED 36WT30/360°/CL/30K/MED/120-277V/V5 - SL®	36	30K	4680	130	360°	80	8.3"	3.7"	120-277	50K	150W	12
91578	LED 36WT30/360°/CL/50K/MED/120-277V/V5 - SL®	36	50K	4680	130	360°	80	8.3"	3.7"	120-277	50K	150W	12
91130	LED 45WT29/320°/CL/50K/MED/120-277V/V4 - SL®	45	50K	4700	104	320°	80	10.4"	3.7"	120-277	50K	150W	12
91693	LED 45WT30/360°/CL/30K/MED/120-277V/V5 - SL®	45	30K	5850	130	360°	80	9.3"	3.7"	120-277	50K	150W	12
91579	LED 45WT30/360°/CL/50K/MED/120-277V/V5 - SL®	45	50K	5850	130	360°	80	9.3"	3.7"	120-277	50K	150W	12
91580	LED 45WT30/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	45	50K	5850	130	360°	82	9.3"	3.7"	120-277	50K	150W	12
91135	LED 52WT29/320°/CL/50K/MOG/120-277V/V4 - SL® DLC	52	50K	4852	93	320°	84	10.4"	3.7"	120-277	50K	180W	12
91569	LED 54WT30/360°/CL/30K/MOG/120-277V/V5 - SL® DLC	54	30K	7020	130	360°	82	10.2"	3.7"	120-277	50K	200W	12
91581	LED 54WT30/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	54	50K	7020	130	360°	82	10.2"	3.7"	120-277	50K	200W	12
91585	LED 65WT30/360°/CL/50K/MOG/120-277V/V5 - SL®	65	50K	8450	130	360°	82	12"	3.7"	120-277	50K	200W	12
91582	LED 75WT30/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	75	50K	9750	130	360°	82	12"	3.7"	120-277	50K	200W	12
91583	LED 100WT44/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	100	50K	13000	130	360°	82	9.6"	5.5"	120-277	50K	400W	6
91584	LED 120WT44/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	120	50K	15600	130	360°	82	10.4"	5.5"	120-277	50K	400W	6
91590	LED 120W HIGH BAY RETROFIT/CL/50K/MOG/120-277V - SL® DLC	120	50K	18000	150	360°	80	8.8"	7.9"	120-277	50K	400W	6



SUITABLE FOR
ENCLOSED
FIXTURES

SUITABLE FOR
DAMP
LOCATIONS

